

Type	Putere (W/m)	Nr.nuclee incalzire	Ecranat	Protectie anti UV	Rezistenta termica a invelisului	Utilizat		Incalzire pardoseala		
						circuit	mat	Incalzire directa	Semi-acumulare	Cu acumulare
ASL1P	10	1	•		70°C	•	•	•		
	15		•			•	•	•		
	18		•			•	•	•		
ADSV	10	2	•		70°C	•		•	•	
	15		•			•	•	•		
	18		•			•	•	•		
ADSV+	10	2	•	•	80°C	•			•	
	18		•	•		•	•	•		
	20		•	•		•	•	•		
ADPSV	10	2	•	•	80°C	•			•	
	18		•	•		•	•	•		
	20		•	•		•	•	•		
PV (P1P)	10	1			70°C	•		•		
	15					•	•			
PSV	10	1	•		70°C	•	•	•		
	15		•			•	•	•		
MAPSV	20	1	•	•	80°C	•	•		•	•
	25		•	•		•	•			
	30		•	•		•	•			
MADPSP	15	2	•	•	90°C 240°C *)	•	•		•	•
	20		•	•		•	•		•	•
	25		•	•		•	•			•
	30		•	•		•	•			
PDSP	28	2	•	•	90°C 200°C *)	•				
PFP	12	2	•	•	70°C	•				
PDS1P	40	2	•		70°C	•				
ELSR-M	10	2	•	•	65°C	•				
	15		•	•		•				
ELSR-N	20	2	•	•	80°C	•				
	30		•	•		•				